## IN THE CLAIMS:

Please amend claims 3, 7 and 8 and add new claims 9, 10 and 11 as follows:

- -3. (Amended) The adjustable support apparatus for monitor in the car as claim 1, wherein the front, middle and rear connecting means are conjugated by a hole, a screw bolt and a nut, and the front connecting means is coupled to the pivotal rod by a hole, a screw bolt and a nut.
- 7. (Amended) The adjustable support apparatus for monitor in the car as claim 1, wherein the front connecting members have a hole at the front opposite a hole of pivotal rod for conjugating by a screw bolt and a nut.
- 8. (Amended) The adjustable support apparatus for monitor in the car as claim 1, wherein the rear connecting members have a hole at the front opposite a hole of second means for conjugating by a screw bolt and a nut.
- 9. (New) The adjustable support apparatus for monitor in the car as claim 2, wherein the front, middle and rear connecting means are conjugated by a hole, a screw bolt and a nut, and the front connecting means is coupled to the pivotal rod by a hole, a screw bolt and a nut.
- 10. (New) The adjustable support apparatus for monitor in the car as claim 6, wherein the front connecting members have a hole at the front opposite a hole of pivotal rod for conjugating by a screw bolt and a nut.
- 11. (New) The adjustable support apparatus for monitor in the car as claim 6, wherein the rear connecting members have a hole at the front opposite a hole of second means for conjugating by a screw bolt and a nut.--